



**TECSEAL**  
**SAFETY DATA SHEET**

**TS100 140CC**

**TS100 380CC**

**TS200 6KG**

**TS200FR 380CC**

**TS300 310CC**



## SAFETY DATA SHEET TS100 140CC

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	LINDAB TECSEAL 100 140CC
Product number	A03321, FP-000232, FP-000233, FP-000234, FP-000235
UFI	UFI: 2469-R0VD-A00M-6EG8

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Adhesive.
Uses advised against	No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

Supplier	APOLLO CHEMICALS LTD SANDY WAY AMINGTON INDUSTRIAL ESTATE TAMWORTH STAFFS B77 4DS T: +44 (0) 1827 54281 F: +44 (0) 1827 53030 E: compliance@apollo.co.uk
----------	--

#### 1.4. Emergency telephone number

Emergency telephone	+44 01827 69662 (NOT 24HRS - 8am-5pm mon-fri )
---------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical hazards	Flam. Liq. 2 - H225
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards	Aquatic Chronic 3 - H412

##### Physicochemical

The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

#### 2.2. Label elements

##### Hazard pictograms



Signal word

Danger

## TS100 140CC

<b>Hazard statements</b>	<p>H225 Highly flammable liquid and vapour.  H315 Causes skin irritation.  H319 Causes serious eye irritation.  H317 May cause an allergic skin reaction.  H361d Suspected of damaging the unborn child.  H336 May cause drowsiness or dizziness.  H373 May cause damage to organs through prolonged or repeated exposure.  H412 Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  P260 Do not breathe vapour/ spray.  P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P308+P313 IF exposed or concerned: Get medical advice/ attention.  P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Supplemental label information</b>	<p>EUH205 Contains epoxy constituents. May produce an allergic reaction.  RCH002a Restricted to professional users.</p>
<b>Contains</b>	<p>TOLUENE, hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane, Formaldehyde, oligomeric reaction products with phenol., ACETONE, ROSIN, REACTION PRODUCT; BISPHENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT&lt;=700)</p>
<b>Supplementary precautionary statements</b>	<p>P201 Obtain special instructions before use.  P202 Do not handle until all safety precautions have been read and understood.  P240 Ground and bond container and receiving equipment.  P241 Use explosion-proof electrical equipment.  P242 Use non-sparking tools.  P243 Take action to prevent static discharges.  P261 Avoid breathing vapour/ spray.  P264 Wash contaminated skin thoroughly after handling.  P271 Use only outdoors or in a well-ventilated area.  P272 Contaminated work clothing should not be allowed out of the workplace.  P273 Avoid release to the environment.  P302+P352 IF ON SKIN: Wash with plenty of water.  P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P312 Call a POISON CENTRE/doctor if you feel unwell.  P314 Get medical advice/ attention if you feel unwell.  P321 Specific treatment (see medical advice on this label).  P332+P313 If skin irritation occurs: Get medical advice/ attention.  P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  P337+P313 If eye irritation persists: Get medical advice/ attention.  P362+P364 Take off contaminated clothing and wash it before reuse.  P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  P403+P233 Store in a well-ventilated place. Keep container tightly closed.  P403+P235 Store in a well-ventilated place. Keep cool.  P405 Store locked up.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

<b>SECTION 3: Composition/information on ingredients</b>
--

**TS100 140CC****3.2. Mixtures**

<b>TOLUENE</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0051
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		
<b>hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35-0001
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>CALOFORT S</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: 471-34-1		
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335		
<b>Formaldehyde, oligomeric reaction products with phenol.</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 9003-35-4	EC number: 500-005-2	REACH registration number: 01-2120735197-51-0000
<b>Classification</b> Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412		

**TS100 140CC**

<b>ACETONE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-0000
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
<b>ANTIMONY TRIOXIDE</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 1309-64-4	EC number: 215-175-0	REACH registration number: 01-2119978287-20-0000
<b>Classification</b> Carc. 2 - H351		
<b>ROSIN</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-0036
<b>Classification</b> Skin Sens. 1 - H317		
<b>HEXANE-norm</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44-0009
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>ZINC OXIDE</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 1314-13-2	EC number: 215-222-5	REACH registration number: 01-2119463881-32-0000
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

**TS100 140CC**

<b>REACTION PRODUCT; BISPENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT&lt;=700)</b>	<b>&lt;1%</b>
CAS number: 25068-38-6                      REACH registration number: 01- 2119456619-26-0004	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	May cause discomfort if swallowed. May cause stomach pain or vomiting.
<b>Skin contact</b>	Prolonged skin contact may cause redness and irritation.
<b>Eye contact</b>	May cause temporary eye irritation.

##### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

##### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m <sup>3</sup> . The product is highly flammable.
-------------------------	---

## TS100 140CC

**Hazardous combustion products** Does not decompose when used and stored as recommended.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

**Special protective equipment for firefighters** Wear chemical protective suit.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### **TOLUENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

#### **CALOFORT S**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

**TS100 140CC****ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

**ANTIMONY TRIOXIDE**

Long-term exposure limit (8-hour TWA): 0.5 mg/m<sup>3</sup>

**HEXANE-norm**

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

**Ingredient comments**

WEL = Workplace Exposure Limits

**TOLUENE (CAS: 108-88-3)****DNEL**

Workers - Inhalation; Long term systemic effects: 192 mg/m<sup>3</sup>

Workers - Inhalation; Long term local effects: 192 mg/m<sup>3</sup>

Workers - Inhalation; Short term systemic effects: 384 mg/m<sup>3</sup>

Workers - Inhalation; Short term local effects: 384 mg/m<sup>3</sup>

Workers - Dermal; Long term systemic effects: 384 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 56.5 mg/m<sup>3</sup>

Consumer - Inhalation; Long term local effects: 56.5 mg/m<sup>3</sup>

Consumer - Inhalation; Short term systemic effects: 226 mg/m<sup>3</sup>

Consumer - Inhalation; Short term local effects: 226 mg/m<sup>3</sup>

Consumer - Dermal; Long term systemic effects: 226 mg/kg/day

Consumer - Oral; Long term systemic effects: 8.13 mg/kg/day

**PNEC**

Fresh water; 0.68 mg/l

marine water; 0.68 mg/l

Intermittent release; 0.68 mg/l

STP; 13.61 mg/l

Sediment (Freshwater); 16.39 mg/kg

Sediment (Marinewater); 16.39 mg/kg

Soil; 2.89 mg/kg

**hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane****Ingredient comments**

WEL = Workplace Exposure Limits

**DNEL**

Consumer - Oral; Long term systemic effects: 699 mg/kg bw/day

Consumer - Dermal; Long term systemic effects: 699 mg/kg bw/day

Workers - Dermal; Long term systemic effects: 773 mg/kg bw/day

Consumer - Inhalation; Long term systemic effects: 608 mg/m<sup>3</sup>

**ACETONE (CAS: 67-64-1)****Ingredient comments**

WEL = Workplace Exposure Limits

**ANTIMONY TRIOXIDE (CAS: 1309-64-4)****DNEL**

- Dermal; Long term systemic effects: 281 mg/kg/day

- Inhalation; Long term local effects: 0.5 mg/m<sup>3</sup>



## TS100 140CC

<b>PNEC</b>	<ul style="list-style-type: none"> <li>- Fresh water; 0.113 mg/l</li> <li>- marine water; 0.0113 mg/l</li> <li>- Sediment (Freshwater); 7.8 mg/kg</li> <li>- Soil; 37 mg/kg</li> <li>- STP; 2.55 mg/l</li> </ul>
-------------	--

### ZINC OXIDE (CAS: 1314-13-2)

<b>DNEL</b>	<p>Workers - Inhalation; Long term local effects: 0.5 mg/m<sup>3</sup></p> <p>General population - Oral; Long term systemic effects: 0.83 mg/kg bw/day</p> <p>General population - Inhalation; Long term systemic effects: 2.5 mg/m<sup>3</sup></p> <p>Workers - Inhalation; Long term systemic effects: 5 mg/m<sup>3</sup></p> <p>General population - Dermal; Long term systemic effects: 83 mg/kg bw/day</p> <p>Workers - Dermal; Long term systemic effects: 83 mg/kg bw/day</p>
<b>PNEC</b>	<p>Fresh water; 0.02036 mg/l</p> <p>marine water; 0.0061 mg/l</p> <p>Sediment (Freshwater); 117 mg/kg</p> <p>STP; 0.052 mg/l</p> <p>Sediment (Marinewater); 56.5 mg/kg</p> <p>Soil; 35.6 mg/kg</p>

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

### Eye/face protection

The following protection should be worn: Chemical splash goggles.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.

### Respiratory protection

In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: ABEK2-P3

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## TS100 140CC

<b>Appearance</b>	Liquid.
<b>Colour</b>	Various colours.
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Estimated value. pH (concentrated solution): 7-8
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	62-100°C @
<b>Flash point</b>	Estimated value. -35°C
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	: 0.6-13%
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	1.10
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	200°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	Not available.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not available.
<b>Comments</b>	Information given is applicable to the product as supplied.
<b>9.2. Other information</b>	
<b>Other information</b>	No information required.
<b>Refractive index</b>	Not available.
<b>Particle size</b>	Not available.
<b>Molecular weight</b>	Not available.
<b>Volatility</b>	Not available.
<b>Saturation concentration</b>	Not available.
<b>Critical temperature</b>	Not available.

## TS100 140CC

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not applicable. Not relevant.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Toxicological information on ingredients.

#### TOLUENE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,580.0

**Species** Rat

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rabbit

##### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 25.7

**Species** Rat

**ATE inhalation (vapours mg/l)** 25.7

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Toxicological effects** No information available.

##### Acute toxicity - oral

**TS100 140CC**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,840.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** Not known. Data lacking.

**ATE oral (mg/kg)** 5,840.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,920.0

**Species** Rat

**Notes (dermal LD<sub>50</sub>)** Data lacking.

**ATE dermal (mg/kg)** 2,920.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 25.2

**Species** Rat

**ATE inhalation (vapours mg/l)** 25.2

**Skin corrosion/irritation**

**Animal data** Data lacking.

**Serious eye damage/irritation**

**Serious eye damage/irritation** Data lacking.

**Aspiration hazard**

**Aspiration hazard** Kinematic viscosity > 20.5 mm<sup>2</sup>/s.

**Inhalation** May cause respiratory system irritation.

**Ingestion** May cause stomach pain or vomiting.

**Skin contact** Irritating to skin.

**Eye contact** May cause severe eye irritation.

**Acute and chronic health hazards** Vapour from this product may be hazardous by inhalation.

**Route of exposure** Inhalation Skin absorption Ingestion. Skin and/or eye contact

**Target organs** No specific target organs known.

**Medical symptoms** Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

**Medical considerations** No information available.

**ACETONE**

**TS100 140CC**

**Other health effects**                    There is no evidence that the product can cause cancer.

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)**                    5,800.0

**Species**                                    Rat

**ATE oral (mg/kg)**                    5,800.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub>  
mg/kg)**                    7,426.0

**Species**                                    Rat

**ATE dermal (mg/kg)**                    7,426.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l)**                    50,100.0

**Species**                                    Rat

**ATE inhalation (vapours  
mg/l)**                                    50,100.0

**Skin corrosion/irritation**

**Extreme pH**                                Slightly irritating.

**Serious eye damage/irritation**

**Serious eye  
damage/irritation**                    Moderately irritating.

**Respiratory sensitisation**

**Respiratory sensitisation**                    Not sensitising.

**ANTIMONY TRIOXIDE****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)**                    5,000.0

**Species**                                    Rat

**ATE oral (mg/kg)**                    5,000.0

**HEXANE-norm****Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)**                    25,000.0

**Species**                                    Rat

**ATE oral (mg/kg)**                    25,000.0

**Acute toxicity - inhalation**

**TS100 140CC**

Acute toxicity inhalation  
(LC<sub>50</sub> gases ppmV) 48,000.0

Species Rat

ATE inhalation (gases  
ppm) 48,000.0

**ZINC OXIDE****Acute toxicity - oral**

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 5,010.0

Species Rat

ATE oral (mg/kg) 5,010.0

**Acute toxicity - dermal**

Acute toxicity dermal (LD<sub>50</sub>  
mg/kg) 2,010.0

Species Mouse

ATE dermal (mg/kg) 2,010.0

**Acute toxicity - inhalation**

Acute toxicity inhalation  
(LC<sub>50</sub> dust/mist mg/l) 5.701

Species Rat

**SECTION 12: Ecological information****Ecological information on ingredients.****hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Ecotoxicity Dangerous for the environment.

**12.1. Toxicity****Ecological information on ingredients.****TOLUENE****Acute aquatic toxicity**

Acute toxicity - fish , 48 hours: > 1-10 mg/l, Freshwater fish

Acute toxicity - aquatic  
invertebrates EC<sub>50</sub>, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic  
plants IC<sub>50</sub>, 72 hours: 100 mg/l, Algae

**hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane****Acute aquatic toxicity**

Acute toxicity - fish LC<sub>50</sub>, hours: >1-<10 mg/l, Fish

**TS100 140CC**

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 3 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** LC<sub>0</sub>, hours: >1-<10 mg/l, Algae

**ACETONE**

**Toxicity** Not considered toxic to fish.

**Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 5540 mg/l, Freshwater fish  
, 96 hours: 11000 mg/l, Marinewater fish  
LC<sub>50</sub>, 96 hours: 11000 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna  
EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** IC<sub>50</sub>, 72 hours: 430 mg/l, Algae

**Acute toxicity - microorganisms** , 30 minutes: 1000 mg/l, Activated sludge

**HEXANE-norm****Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Fish

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Algae

**ZINC OXIDE****Acute aquatic toxicity**

**LE(C)<sub>50</sub>** 0.1 < L(E)C<sub>50</sub> ≤ 1

**M factor (Acute)** 1

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1.1 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 0.098 mg/l, Daphnia magna

**Chronic aquatic toxicity**

**M factor (Chronic)** 1

**REACTION PRODUCT; BISPHENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT<=700)****Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 1.8 mg/l, Daphnia magna

**TS100 140CC**

<b>Acute toxicity - aquatic plants</b>	EC <sub>50</sub> , 72 hours: 11 mg/l, Freshwater algae
<b>Acute toxicity - microorganisms</b>	IC <sub>50</sub> , 18 hours: 42.6 mg/l, Bacteria
<b>Chronic aquatic toxicity</b>	
<b>Chronic toxicity - aquatic invertebrates</b>	NOEC, 21 days: 0.3 mg/l, Daphnia magna

**12.2. Persistence and degradability****Ecological information on ingredients.****ACETONE**

<b>Persistence and degradability</b>	The product is expected to be biodegradable.
--------------------------------------	--

**12.3. Bioaccumulative potential**

<b>Partition coefficient</b>	Not available.
------------------------------	----------------

**Ecological information on ingredients.****TOLUENE**

<b>Bioaccumulative potential</b>	The product does not contain any substances expected to be bioaccumulating.
<b>Partition coefficient</b>	Not available.

**ACETONE**

<b>Bioaccumulative potential</b>	The product does not contain any substances expected to be bioaccumulating. BCF: 3,
<b>Partition coefficient</b>	Pow: < -0.24

**REACTION PRODUCT; BISPHENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT<=700)**

<b>Partition coefficient</b>	log Pow: 3.242
------------------------------	----------------

**12.4. Mobility in soil**

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

**Ecological information on ingredients.****TOLUENE**

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

**ACETONE**

<b>Mobility</b>	The product is miscible with water and may spread in water systems.
<b>Adsorption/desorption coefficient</b>	Water - log Koc: 1.5 @ 20°C



**TS100 140CC**

Henry's law constant 2929-3070 Pa m<sup>3</sup>/mol @ 25°C

**REACTION PRODUCT; BISPHENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT<=700)**

Henry's law constant 4.93E-05 Pa m<sup>3</sup>/mol @ 25°C

**12.5. Results of PBT and vPvB assessment**

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

**Ecological information on ingredients.****TOLUENE**

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

**ACETONE**

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

**12.6. Other adverse effects**

**Other adverse effects** None known.

**Ecological information on ingredients.****TOLUENE**

**Other adverse effects** Not known.

**ACETONE**

**Other adverse effects** Not applicable.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**General information** Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**SECTION 14: Transport information****14.1. UN number**

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (ADN) 1133

**14.2. UN proper shipping name**

**Proper shipping name (ADR/RID)** ADHESIVES

**TS100 140CC**

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

**14.3. Transport hazard class(es)**

ADR/RID class 3  
 ADR/RID classification code F1  
 ADR/RID label 3  
 IMDG class 3  
 ICAO class/division 3  
 ADN class 3

**Transport labels****14.4. Packing group**

ADR/RID packing group II  
 IMDG packing group II  
 ICAO packing group II  
 ADN packing group II

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

**14.6. Special precautions for user**

EmS F-E, S-D  
 ADR transport category 2  
 Hazard Identification Number (ADR/RID) 33  
 Tunnel restriction code (D/E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code****SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**National regulations** Health and Safety at Work etc. Act 1974 (as amended).  
 The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).  
 The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).  
 Control of Substances Hazardous to Health Regulations 2002 (as amended).

## TS100 140CC

**EU legislation** Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work.  
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

**Authorisations (Annex XIV Regulation 1907/2006)** This product is/contains a substance that is included in REGULATION (EC) No 1907/2006 (REACH) ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES. Entry number: 48

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Issued by</b>	Compliance
<b>Revision date</b>	19/10/2021
<b>Revision</b>	22
<b>Supersedes date</b>	29/09/2020
<b>Hazard statements in full</b>	<p>H225 Highly flammable liquid and vapour.  H304 May be fatal if swallowed and enters airways.  H315 Causes skin irritation.  H317 May cause an allergic skin reaction.  H319 Causes serious eye irritation.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H351 Suspected of causing cancer.  H361d Suspected of damaging the unborn child.  H361f Suspected of damaging fertility.  H373 May cause damage to organs through prolonged or repeated exposure.  H400 Very toxic to aquatic life.  H410 Very toxic to aquatic life with long lasting effects.  H411 Toxic to aquatic life with long lasting effects.  H412 Harmful to aquatic life with long lasting effects.</p>
<b>Store Between</b>	Store Between 5°C-25°C

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



## SAFETY DATA SHEET TS100 380CC

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** LINDAB TECSEAL 100 380CC  
**Product number** A00048, FP-000051, FP-000052, FP-000056, FP-000057

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Adhesive.  
**Uses advised against** No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** APOLLO CHEMICALS LTD  
 SANDY WAY  
 AMINGTON INDUSTRIAL ESTATE  
 TAMWORTH  
 STAFFS  
 B77 4DS  
 T: +44 (0) 1827 54281  
 F: +44 (0) 1827 53030  
 E: compliance@apollo.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone** +44 01827 69662 (NOT 24HRS - 8am-5pm mon-fri )

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 2 - H225  
**Health hazards** Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373  
**Environmental hazards** Aquatic Chronic 3 - H412

**Physicochemical** The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

#### 2.2. Label elements

##### Hazard pictograms



**Signal word**

Danger

## TS100 380CC

<b>Hazard statements</b>	<p>H225 Highly flammable liquid and vapour.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H361d Suspected of damaging the unborn child.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P260 Do not breathe vapours.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P313 Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Supplemental label information</b>	<p>EUH205 Contains epoxy constituents. May produce an allergic reaction.</p> <p>RCH002a Restricted to professional users.</p>
<b>Contains</b>	<p>TOLUENE, hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane, Formaldehyde, oligomeric reaction products with phenol., ACETONE, ROSIN, EPOXY RESIN (Number average MW &lt;= 700 )</p>
<b>Supplementary precautionary statements</b>	<p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p>

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**TS100 380CC**

<b>TOLUENE</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0051
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		
<b>hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35-0001
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>Formaldehyde, oligomeric reaction products with phenol.</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 9003-35-4	EC number: 500-005-2	REACH registration number: 01-2120735197-51-0000
<b>Classification</b> Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412		
<b>ACETONE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-0000
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		

**TS100 380CC**

<b>ZINC OXIDE</b> <1%		
CAS number: 1314-13-2	EC number: 215-222-5	REACH registration number: 01-2119463881-32-0000
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
<b>ROSIN</b> <1%		
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-0036
<b>Classification</b> Skin Sens. 1 - H317		
<b>ANTIMONY TRIOXIDE</b> <1%		
CAS number: 1309-64-4	EC number: 215-175-0	REACH registration number: 01-2119978287-20-0000
<b>Classification</b> Carc. 2 - H351		
<b>HEXANE-norm</b> <1%		
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44-0009
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
<b>EPOXY RESIN (Number average MW ≤ 700 )</b> <1%		
CAS number: 25068-38-6	EC number: 500-033-5	REACH registration number: 01-2119456619-26-0016
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		

The full text for all hazard statements is displayed in Section 16.

**SECTION 4: First aid measures**

## TS100 380CC

### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	May cause discomfort if swallowed. May cause stomach pain or vomiting.
<b>Skin contact</b>	Prolonged skin contact may cause redness and irritation.
<b>Eye contact</b>	May cause temporary eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Heating may generate flammable vapours. The product is highly flammable.
<b>Hazardous combustion products</b>	Does not decompose when used and stored as recommended.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.
<b>Special protective equipment for firefighters</b>	Wear chemical protective suit.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up



## TS100 380CC

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **TOLUENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m<sup>3</sup>

Sk

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **ANTIMONY TRIOXIDE**

Long-term exposure limit (8-hour TWA): 0.5 mg/m<sup>3</sup>

##### **HEXANE-norm**

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

**Ingredient comments** WEL = Workplace Exposure Limits

**TOLUENE (CAS: 108-88-3)**

**TS100 380CC**

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 192 mg/m <sup>3</sup> Workers - Inhalation; Long term local effects: 192 mg/m <sup>3</sup> Workers - Inhalation; Short term systemic effects: 384 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 384 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 384 mg/kg/day Consumer - Inhalation; Long term systemic effects: 56.5 mg/m <sup>3</sup> Consumer - Inhalation; Long term local effects: 56.5 mg/m <sup>3</sup> Consumer - Inhalation; Short term systemic effects: 226 mg/m <sup>3</sup> Consumer - Inhalation; Short term local effects: 226 mg/m <sup>3</sup> Consumer - Dermal; Long term systemic effects: 226 mg/kg/day Consumer - Oral; Long term systemic effects: 8.13 mg/kg/day
<b>PNEC</b>	Fresh water; 0.68 mg/l marine water; 0.68 mg/l Intermittent release; 0.68 mg/l STP; 13.61 mg/l Sediment (Freshwater); 16.39 mg/kg Sediment (Marinewater); 16.39 mg/kg Soil; 2.89 mg/kg

**hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane**

<b>Ingredient comments</b>	WEL = Workplace Exposure Limits
<b>DNEL</b>	Consumer - Oral; Long term systemic effects: 699 mg/kg bw/day Consumer - Dermal; Long term systemic effects: 699 mg/kg bw/day Workers - Dermal; Long term systemic effects: 773 mg/kg bw/day Consumer - Inhalation; Long term systemic effects: 608 mg/m <sup>3</sup>

**ACETONE (CAS: 67-64-1)**

<b>Ingredient comments</b>	WEL = Workplace Exposure Limits
----------------------------	---------------------------------

**ZINC OXIDE (CAS: 1314-13-2)**

<b>DNEL</b>	Workers - Inhalation; Long term local effects: 0.5 mg/m <sup>3</sup> General population - Oral; Long term systemic effects: 0.83 mg/kg bw/day General population - Inhalation; Long term systemic effects: 2.5 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects: 5 mg/m <sup>3</sup> General population - Dermal; Long term systemic effects: 83 mg/kg bw/day Workers - Dermal; Long term systemic effects: 83 mg/kg bw/day
<b>PNEC</b>	Fresh water; 0.02036 mg/l marine water; 0.0061 mg/l Sediment (Freshwater); 117 mg/kg STP; 0.052 mg/l Sediment (Marinewater); 56.5 mg/kg Soil; 35.6 mg/kg

**ANTIMONY TRIOXIDE (CAS: 1309-64-4)**

<b>DNEL</b>	- Dermal; Long term systemic effects: 281 mg/kg/day - Inhalation; Long term local effects: 0.5 mg/m <sup>3</sup>
-------------	---

## TS100 380CC

<b>PNEC</b>	- Fresh water; 0.113 mg/l
	- marine water; 0.0113 mg/l
	- Sediment (Freshwater); 7.8 mg/kg
	- Soil; 37 mg/kg
	- STP; 2.55 mg/l

### EPOXY RESIN (Number average MW <= 700 ) (CAS: 25068-38-6)

<b>DNEL</b>	Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day
	Industry - Inhalation; Short term systemic effects: 12.25 mg/m <sup>3</sup>
	Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 12.25 mg/m <sup>3</sup>
	Consumer - Dermal; Short term systemic effects: 3.571 mg/kg/day
	Consumer - Oral; Short term systemic effects: 0.75 mg/kg/day
	Consumer - Dermal; Long term systemic effects: 3.751 mg/kg/day
	Consumer - Oral; Long term systemic effects: 0.75 mg/kg/day

<b>PNEC</b>	- Fresh water; 0.006 mg/l
	- marine water; 0.0006 mg/l
	- Intermittent release; 0.018 mg/l
	- STP; 10 mg/l
	- Sediment (Freshwater); 0.996 mg/l
	- Sediment (Marinewater); 0.0996 mg/l
- Soil; 0.196 mg/kg	

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

### Eye/face protection

The following protection should be worn: Chemical splash goggles.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.

### Respiratory protection

In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: ABEK2-P3

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**TS100 380CC**

<b>Appearance</b>	Paste.
<b>Colour</b>	Grey.
<b>Odour</b>	aromatic hydrocarbons
<b>Odour threshold</b>	Not available.
<b>pH</b>	Estimated value. pH (concentrated solution): 7-8
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	62-100°C @
<b>Flash point</b>	Estimated value. -35°C
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	: 0.6-13%
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	1.14 @ 20°C
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	200°C
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Kinematic viscosity > 20.5 mm <sup>2</sup> /s.
<b>Explosive properties</b>	Not available.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not available.
<b>Comments</b>	Information given is applicable to the product as supplied.
<b><u>9.2. Other information</u></b>	
<b>Other information</b>	No information required.
<b>Refractive index</b>	Not available.
<b>Particle size</b>	Not available.
<b>Molecular weight</b>	Not available.
<b>Volatility</b>	Not available.
<b>Saturation concentration</b>	Not available.
<b>Critical temperature</b>	Not available.

## TS100 380CC

**Volatile organic compound** This product contains a maximum VOC content of 480 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

#### 10.2. Chemical stability

**Stability** No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not applicable. Not relevant.

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

#### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Strong acids. Strong alkalis.

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Inhalation** Harmful by inhalation.

**Ingestion** Harmful if swallowed.

**Skin contact** Harmful in contact with skin.

#### Toxicological information on ingredients.

#### TOLUENE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,580.0

**Species** Rat

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rabbit

##### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 25.7

**Species** Rat

**TS100 380CC**

**ATE inhalation (vapours  
mg/l)** 25.7

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Toxicological effects** No information available.

Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)** 5,840.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** Not known. Data lacking.

**ATE oral (mg/kg)** 5,840.0

Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub>  
mg/kg)** 2,920.0

**Species** Rat

**Notes (dermal LD<sub>50</sub>)** Data lacking.

**ATE dermal (mg/kg)** 2,920.0

Acute toxicity - inhalation

**Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l)** 25.2

**Species** Rat

**ATE inhalation (vapours  
mg/l)** 25.2

Skin corrosion/irritation

**Animal data** Data lacking.

Serious eye damage/irritation

**Serious eye  
damage/irritation** Data lacking.

Aspiration hazard

**Aspiration hazard** Kinematic viscosity > 20.5 mm<sup>2</sup>/s.

**Inhalation** May cause respiratory system irritation.

**Ingestion** May cause stomach pain or vomiting.

**Skin contact** Irritating to skin.

**Eye contact** May cause severe eye irritation.

**Acute and chronic health  
hazards** Vapour from this product may be hazardous by inhalation.

**Route of exposure** Inhalation Skin absorption Ingestion. Skin and/or eye contact

## TS100 380CC

<b>Target organs</b>	No specific target organs known.
<b>Medical symptoms</b>	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
<b>Medical considerations</b>	No information available.

### ACETONE

**Other health effects**                      There is no evidence that the product can cause cancer.

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)**                                      5,800.0

**Species**                                      Rat

**ATE oral (mg/kg)**                              5,800.0

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub>  
mg/kg)**                                      7,426.0

**Species**                                      Rat

**ATE dermal (mg/kg)**                              7,426.0

#### Acute toxicity - inhalation

**Acute toxicity inhalation  
(LC<sub>50</sub> vapours mg/l)**                              50,100.0

**Species**                                      Rat

**ATE inhalation (vapours  
mg/l)**                                      50,100.0

#### Skin corrosion/irritation

**Extreme pH**                                      Slightly irritating.

#### Serious eye damage/irritation

**Serious eye  
damage/irritation**                              Moderately irritating.

#### Respiratory sensitisation

**Respiratory sensitisation**                      Not sensitising.

### ZINC OXIDE

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub>  
mg/kg)**                                      5,010.0

**Species**                                      Rat

**ATE oral (mg/kg)**                              5,010.0

#### Acute toxicity - dermal

**TS100 380CC**

**Acute toxicity dermal (LD<sub>50</sub> 2,010.0 mg/kg)**

**Species** Mouse

**ATE dermal (mg/kg)** 2,010.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l)** 5.701

**Species** Rat

**ANTIMONY TRIOXIDE**

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

**ATE oral (mg/kg)** 5,000.0

**HEXANE-norm**

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 25,000.0

**Species** Rat

**ATE oral (mg/kg)** 25,000.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> gases ppmV)** 48,000.0

**Species** Rat

**ATE inhalation (gases ppm)** 48,000.0

**EPOXY RESIN (Number average MW <= 700 )**

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 15,000.0

**Species** Rat

**ATE oral (mg/kg)** 15,000.0

**Acute toxicity - dermal**

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 23,000.0

**Species** Rabbit

**ATE dermal (mg/kg)** 23,000.0



**TS100 380CC****SECTION 12: Ecological information**Ecological information on ingredients.hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Ecotoxicity** Dangerous for the environment.

**12.1. Toxicity**Ecological information on ingredients.**TOLUENE**Acute aquatic toxicity

**Acute toxicity - fish** , 48 hours: > 1-10 mg/l, Freshwater fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 11.5 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** IC<sub>50</sub>, 72 hours: 100 mg/l, Algae

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexaneAcute aquatic toxicity

**Acute toxicity - fish** LC<sub>0</sub>, hours: >1-<10 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 3 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** LC<sub>0</sub>, hours: >1-<10 mg/l, Algae

**ACETONE**

**Toxicity** Not considered toxic to fish.

Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 5540 mg/l, Freshwater fish  
, 96 hours: 11000 mg/l, Marinewater fish  
LC<sub>50</sub>, 96 hours: 11000 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna  
EC<sub>50</sub>, 48 hours: 8800 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** IC<sub>50</sub>, 72 hours: 430 mg/l, Algae

**Acute toxicity - microorganisms** , 30 minutes: 1000 mg/l, Activated sludge

**ZINC OXIDE**Acute aquatic toxicity

**LE(C)<sub>50</sub>** 0.1 < L(E)C<sub>50</sub> ≤ 1

**M factor (Acute)** 1

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1.1 mg/l, Oncorhynchus mykiss (Rainbow trout)

**TS100 380CC**

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 0.098 mg/l, Daphnia magna

**Chronic aquatic toxicity**

**M factor (Chronic)** 1

**HEXANE-norm****Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Fish

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** LC<sub>50</sub>, EC<sub>50</sub>, IC<sub>50</sub> : 10 mg/l, Algae

**EPOXY RESIN (Number average MW <= 700 )****Acute aquatic toxicity**

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 1.8 mg/l,

**Chronic aquatic toxicity**

**Chronic toxicity - aquatic invertebrates** NOEC, 21 days: 0.3 mg/l, Daphnia magna

**12.2. Persistence and degradability****Ecological information on ingredients.****ACETONE**

**Persistence and degradability** The product is expected to be biodegradable.

**12.3. Bioaccumulative potential**

**Partition coefficient** Not available.

**Ecological information on ingredients.****TOLUENE**

**Bioaccumulative potential** The product does not contain any substances expected to be bioaccumulating.

**Partition coefficient** Not available.

**ACETONE**

**Bioaccumulative potential** The product does not contain any substances expected to be bioaccumulating. BCF: 3,

**Partition coefficient** Pow: < -0.24

**EPOXY RESIN (Number average MW <= 700 )**

**Bioaccumulative potential** BCF: 100,

## TS100 380CC

**Partition coefficient**                      log Pow: 3.242

### 12.4. Mobility in soil

**Mobility**                                      The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### Ecological information on ingredients.

#### TOLUENE

**Mobility**                                      The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### ACETONE

**Mobility**                                      The product is miscible with water and may spread in water systems.

**Adsorption/desorption coefficient**                      Water - log Koc: 1.5 @ 20°C

**Henry's law constant**                      2929-3070 Pa m<sup>3</sup>/mol @ 25°C

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment**                      This product does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

#### TOLUENE

**Results of PBT and vPvB assessment**                      This product does not contain any substances classified as PBT or vPvB.

#### ACETONE

**Results of PBT and vPvB assessment**                      This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects**                      None known.

### Ecological information on ingredients.

#### TOLUENE

**Other adverse effects**                      Not known.

#### ACETONE

**Other adverse effects**                      Not applicable.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information**                      Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**                              Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**TS100 380CC****SECTION 14: Transport information****14.1. UN number**

UN No. (ADR/RID)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133

**14.2. UN proper shipping name**

Proper shipping name (ADR/RID)	ADHESIVES
Proper shipping name (IMDG)	ADHESIVES
Proper shipping name (ICAO)	ADHESIVES
Proper shipping name (ADN)	ADHESIVES

**14.3. Transport hazard class(es)**

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3

**Transport labels****14.4. Packing group**

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

**14.5. Environmental hazards**

Environmentally hazardous substance/marine pollutant  
No.

**14.6. Special precautions for user**

EmS	F-E, S-D
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code****SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

## TS100 380CC

<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
<b>Authorisations (Annex XIV Regulation 1907/2006)</b>	This product is/contains a substance that is included in REGULATION (EC) No 1907/2006 (REACH) ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES.
<b>Restrictions (Annex XVII Regulation 1907/2006)</b>	Entry number: 48

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Issued by</b>	Compliance
<b>Revision date</b>	03/11/2021
<b>Revision</b>	21
<b>Supersedes date</b>	04/06/2021
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
<b>Store Between</b>	Store Between 5°C-25°C
<b>Contains isocyanate</b>	NO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

**LINDAB HIGH VELOCITY BRUSHABLE ACRYLIC DUCT SEALANT**  
Supersedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier**

**Product Name** LINDAB HIGH VELOCITY BRUSHABLE ACRYLIC DUCT SEALANT  
**Pure substance/mixture** Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Recommended use** Sealant.  
**Uses advised against** Not to be used in production of toys or childcare articles

**1.3. Details of the supplier of the safety data sheet****Company Name**

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

**1.4. Emergency telephone number**

**United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Not classified

**2.2. Label Elements**

Not classified

**Signal word**

None

**Hazard statements**

Not classified

**EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

**Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P280 - Wear protective gloves and eye/face protection.

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

## 2.3. Other Hazards

No information available

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	Carc. 2 (H351i)		01-2119489379-17-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.0015 - <0.01	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1)	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX

**Full text of H- and EUH-phrases: see section 16**

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.



# SAFETY DATA SHEET

BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

**Other information** Ventilate the area. Prevent further leakage or spillage if safe to do so.  
**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Diisononyl phthalate 28553-12-0	-	TWA: 5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

### **Derived No Effect Level (DNEL)**

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

<b>Derived No Effect Level (DNEL)</b>			
<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.  
(PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

# SAFETY DATA SHEET

BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT  
Supersedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

## Personal Protective Equipment

**Eye/face protection**

Tight sealing safety goggles.

**Hand protection**

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

**Skin and body protection**

Suitable protective clothing.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Paste / Gel Liquid
<b>Appearance</b>	Paste
<b>Colour</b>	Multiple Colours
<b>Odour</b>	Characteristic
<b>Odour threshold</b>	No information available

Property	Values	Remarks • Method
<b>pH</b>	No data available	
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	100 °C	
<b>Flash point</b>	No data available	
<b>Evaporation rate</b>	No data available	
<b>Flammability (solid, gas)</b>	Not applicable for liquids	
<b>Flammability Limit in Air</b>		
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapour pressure</b>	No data available	
<b>Vapour density</b>	No data available	
<b>Relative density</b>	No data available	
<b>Water solubility</b>	Immiscible in water	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>	No data available	
<b>Kinematic viscosity</b>	No data available	
<b>Dynamic viscosity</b>	No data available	
<b>Explosive properties</b>	No data available	
<b>Oxidising properties</b>	No data available	

### 9.2. Other information

<b>Solid content (%)</b>	No information available
<b>VOC Content (%)</b>	6.3 g/L / 0.26 %
<b>Density</b>	1.64 g/cm <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No information available.

# SAFETY DATA SHEET

BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

## 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

## 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Numerical measures of toxicity

##### Acute toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	
---	--------------------	---	--

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of	EC50 (72h)	EC50 (96h) =	-	EC50 (48h) =0.1	100	100

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	0.22 mg/L (Oncorhynchus mykiss) (OECD 211)		mg/L (Daphnia magna) (OECD 202)		
--	--	--	--	---------------------------------	--	--

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.7	6.95
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Do not reuse empty containers. Handle contaminated packages in the same way as the

# SAFETY DATA SHEET

BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

product itself.

## Other information

Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant Np  
14.6 Special Provisions None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	16389-88-1
Water	7732-18-5
Styrene acrylic co-polymer emulsion	UNKNOWN
Diisononyl phthalate	28553-12-0
Isotridecanol, ethoxylated	UNKNOWN
Titanium dioxide	13463-67-7
Ferric oxide black	1317-61-9
Polycarboxylate in aqueous solution	UNKNOWN
1,2-Propylene glycol	57-55-6
Sodium phosphate dibasic	7558-79-4
Thixol liquid acrylic thickener	UNKNOWN

# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supersedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

Acrylic Latex thickener	UNKNOWN
Sodium hydroxide	1310-73-2
Iron oxide yellow	51274-00-1
1,2-benzisothiazol-3(2H)-one [BIT]	2634-33-5
2-Propenoic acid, sodium salt	7446-81-3
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	55965-84-9
Sodium nitrate	7631-99-4

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	16389-88-1	
Water	7732-18-5	
Styrene acrylic co-polymer emulsion	UNKNOWN	
Diisononyl phthalate	28553-12-0	52[a].
Isotridecanol, ethoxylated	UNKNOWN	
Titanium dioxide	13463-67-7	
Ferric oxide black	1317-61-9	
Polycarboxylate in aqueous solution	UNKNOWN	
1,2-Propylene glycol	57-55-6	
Sodium phosphate dibasic	7558-79-4	
Thixol liquid acrylic thickener	UNKNOWN	
Acrylic Latex thickener	UNKNOWN	
Sodium hydroxide	1310-73-2	
Iron oxide yellow	51274-00-1	
1,2-benzisothiazol-3(2H)-one [BIT]	2634-33-5	
2-Propenoic acid, sodium salt	7446-81-3	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	55965-84-9	
Sodium nitrate	7631-99-4	

**52** . Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information



# SAFETY DATA SHEET

**BOSTIK IDENDEN 40-320 HIGH VELOCITY BRUSHABLE  
ACRYLIC DUCT SEALANT**  
Supercedes Date: 29-Sep-2020

Revision Date: 08-Oct-2020

Revision Number 1.02

---

## Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H310 - Fatal in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects

### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date:** 08-Oct-2020

### Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**

**LINDAB TECSEAL 200 FRA**  
Supersedes Date: 14-Aug-2020**Revision Date:** 08-Oct-2020  
**Revision Number** 1.03**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** LINDAB TECSEAL 200 FRA  
**Pure substance/mixture** Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Sealant.  
**Uses advised against** Not to be used in production of toys or childcare articles**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Not classified

**2.2. Label Elements**

Not classified

**Signal word**

None

**Hazard statements**

Not classified

**EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] &amp; 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

**Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P280 - Wear protective gloves and eye/face protection.

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
 Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
 Revision Number 1.03

## 2.3. Other Hazards

No information available

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Titanium dioxide	236-675-5	13463-67-7	1- <2.5	Carc. 2 (H351i)		01-2119489379-17-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.0015 - <0.01	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1)	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX

Full text of H- and EUH-phrases: see section 16

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of toxic and corrosive gases/vapours.
<b>Hazardous combustion products</b>	Carbon dioxide (CO <sub>2</sub> ).

### 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.
<b>Other information</b>	Ventilate the area. Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Diisononyl phthalate 28553-12-0	-	TWA: 5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
 Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
 Revision Number 1.03

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.  
 (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face protection** Tight sealing safety goggles.  
**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.  
**Skin and body protection** Suitable protective clothing.  
**Respiratory protection** Ensure adequate ventilation, especially in confined areas.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Solid  
**Appearance** Paste  
**Colour** Grey  
**Odour** Characteristic  
**Odour threshold** No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	> 34 °C	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Immiscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	420 °C	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

### 9.2. Other information

**Solid content (%)** No information available  
**VOC Content (%)** 6.2 g/L / 0.27 %  
**Density** 1.67 g/cm<sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No information available.

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supercedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

## 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** None known based on information supplied.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### **Product Information**

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Numerical measures of toxicity

##### **Acute toxicity**

##### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	
reaction mass of	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg	



# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
 Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
 Revision Number 1.03

5-chloro-2-methyl-2H-isothiazol-1-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9		(Oryctolagus cuniculus)	
--	--	-------------------------	--

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

#### **Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-is	EC50 (72h) =0.048 mg/L	EC50 (96h) = 0.22 mg/L	-	EC50 (48h) =0.1 mg/L (Daphnia	100	100

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner iella subcapitata) (OECD 201)	(Oncorhynchus mykiss) (OECD 211)		magna) (OECD 202)		
--	--	--	--	----------------------	--	--

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.7	6.95
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

**European Waste Catalogue** 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant Np  
14.6 Special Provisions None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	16389-88-1
Water	7732-18-5
Styrene acrylic co-polymer emulsion	UNKNOWN
Diisononyl phthalate	28553-12-0
Titanium dioxide	13463-67-7

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

Isotridecanol, ethoxylated	UNKNOWN
Ferric oxide black	1317-61-9
Polycarboxylate in aqueous solution	UNKNOWN
1,2-Propylene glycol	57-55-6
Thixol liquid acrylic thickener	UNKNOWN
Acrylic Latex thickener	UNKNOWN
Sodium phosphate dibasic	7558-79-4
Sodium hydroxide	1310-73-2
Iron oxide yellow	51274-00-1
1,2-benzisothiazol-3(2H)-one [BIT]	2634-33-5
2-Propenoic acid, sodium salt	7446-81-3
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	55965-84-9
Sodium nitrate	7631-99-4

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	16389-88-1	
Water	7732-18-5	
Styrene acrylic co-polymer emulsion	UNKNOWN	
Diisononyl phthalate	28553-12-0	52[a].
Titanium dioxide	13463-67-7	
Isotridecanol, ethoxylated	UNKNOWN	
Ferric oxide black	1317-61-9	
Polycarboxylate in aqueous solution	UNKNOWN	
1,2-Propylene glycol	57-55-6	
Thixol liquid acrylic thickener	UNKNOWN	
Acrylic Latex thickener	UNKNOWN	
Sodium phosphate dibasic	7558-79-4	
Sodium hydroxide	1310-73-2	
Iron oxide yellow	51274-00-1	
1,2-benzisothiazol-3(2H)-one [BIT]	2634-33-5	
2-Propenoic acid, sodium salt	7446-81-3	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	55965-84-9	
Sodium nitrate	7631-99-4	

52 . Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

### 15.2. Chemical safety assessment

# SAFETY DATA SHEET

LINDAB TECSEAL 200 FRA  
Supersedes Date: 14-Aug-2020

Revision Date: 08-Oct-2020  
Revision Number 1.03

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H310 - Fatal in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H411 - Toxic to aquatic life with long lasting effects

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

#### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date:** 08-Oct-2020

#### **Indication of changes**

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**

**LINDAB TECSEAL 300 TRANSLUCENT**  
Supersedes Date: 19-Oct-2020Revision date 20-Oct-2021  
Revision Number 2**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product Name** LINDAB TECSEAL 300 TRANSLUCENT  
**Pure substance/mixture** Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Sealant.  
**Uses advised against** None known**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

**Chronic aquatic toxicity** Category 3 - (H412)**2.2. Label elements****Signal word**  
None**Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

**EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

**Precautionary Statements - EU (§28, 1272/2008)**P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P273 - Avoid release to the environment  
P501 - Dispose of contents/ container to an approved waste disposal plant**2.3. Other hazards**

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

**PBT & vPvB**

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	40 - <80	Asp. Tox. 1 (H304)		01-2119827000-58-XXXX
Triacetoxyp(propyl)silane	241-816-9	17865-07-5	1- <2.5	Skin Corr. 1B (H314) (EUH071)		01-2119966899-07-XXXX
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	264-843-8	64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (H410) M=100 (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	-

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

**Skin contact** Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

**Ingestion** Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

## **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

## **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### **6.2. Environmental precautions**

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### **6.4. Reference to other sections**

**Reference to other sections** See section 8 for more information. See section 13 for more information.



# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

Chemical name	European Union	United Kingdom
Acetic acid 64-19-7	TWA: 25 mg/m <sup>3</sup> TWA: 10 ppm STEL: 50 mg/m <sup>3</sup> STEL: 20 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 20 ppm STEL: 50 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)** No information available.

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

**Skin and body protection** None under normal use conditions.

**Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Recommended filter type: especially in confined areas.  
Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Clear, colourless
Odour	Acetic acid
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	0.94	
Water solubility	Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	> 21 mm <sup>2</sup> /s	@ 40°C
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

### 9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Density	0.94 g/cm <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Numerical measures of toxicity

##### Acute toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 (Rattus)
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal		6 days	Product score <=1 Non-irritant

**Serious eye damage/eye irritation** By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye		6 days	Product score <=1 Non-irritant

**Respiratory or skin sensitisation** May produce an allergic reaction. No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
 Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
 Revision Number 2

## 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h) > 3193 mg/l (Acartia tonsa)		
Triacetoxyl(propyl)silane 17865-07-5	EC50 (72h): approx. 24 mg/l (Pseudokirchneriella subspicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	EC50 (72h) = 0.025 mg/L Algae (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems		Half-life	1.1-1.3 days

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Triacetoxyl(propyl)silane 17865-07-5	1.23	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	4.4	13

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	The substance is not PBT / vPvB

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Triacetoxy(propyl)silane 17865-07-5	The substance is not PBT / vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	The substance is not PBT / vPvB

## 12.6. Other adverse effects

Other adverse effects No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

CCL TECSEAL 300 TRANSLUCENT  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## European Union

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

EUH071 - Corrosive to the respiratory tract  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure

# SAFETY DATA SHEET

**CCL TECSEAL 300 TRANSLUCENT**  
**Supersedes Date:** 19-Oct-2020

**Revision date** 20-Oct-2021  
**Revision Number** 2

---

EWC European Waste Catalogue

**Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 20-Oct-2021

**Indication of changes**

**Revision note** SDS sections updated, 2, 3, 11, 12, 13, 15, 16.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**