

Lindab Standing Seam Roofing

Timeless, moldable and exclusive roofing from Lindab in many materials and colours





We simplify construction

At Lindab we are driven by a strong desire to continuously generate improvements and to simplify construction. We do that by developing products and systems that are easy to use and energy efficient, together with industry-leading knowledge, support, logistics and efficient availability.

We want to simplify everything – from designing, ordering, delivery, goal achievement and installation to the entire way of doing business with us. By simplifying in every stage of the construction process, we also contribute to energy-efficiency.

Timeless material for standing seam roofing from Lindab

Sheet metal is a timeless, moldable and exclusive roofing material, which has been appreciated for centuries. It requires virtually no maintenance and its natural beauty is a joy to behold for many, many years.

Choosing Lindab's standing seam roofing not only means that your roof will blend in equally well with old, listed buildings and ultra-modern houses. It also means that you will have access to our knowledge and support to make your design and construction work easier and more exact.

Lindab Standing seam roofing in a nutshell

- moldable
- fits both listed and modern buildings
- virtually no maintenance
- long lasting
- a wide range of colours and materials
- a wide range of accessories that simplifies the mounting

See our wide colour rage on lindab.co.uk/colours



GreenCoat[©]

A new generation more environmentally friendly structured high build polyester coating

GreenCoat® in PLX and FAP is a high build polyester with a slightly structured surface. The nominal coating thickness is 36 µm. The beads in the paint makes the surface more scratch resistant compared to a smooth coating. A substantial part of the solvents has also been replaced by renewable alternatives, most commonly Swedish rapeseed oil. The rapeseed oil reacts into the paint when cured and that makes it possible to use a polyester binder that gives a very flexible coating with improved colour and gloss retention.

Lindab is official GreenCoat® Partner. GreenCoat® is the brand for SSAB for innovative, sustainable color coated steel solutions for roofs, façades and rainwater systems.

Colours

GreenCoat is available in matt (gloss 10) or glossy (gloss 40) finish. All available colours are specified on page 7.

On the backing coat, you find arrows so that you always can keep track of the coils direction. Make sure you always mount metallic colours in the same direction. Otherwise the flakes in the paint that creates the metallic effect, can brake light in difference ways, with an experienced colour difference as a result.

Warranties

Read more about warranty periods on lindabprofile.co.uk





GREENCOAT®

COLORFUL STEEL



Sustainable building with GreenCoat®

GreenCoat® colour coated steels stand at the forefront of sustainable building trends worldwide. With numerous advantages over traditional materials like zinc and aluminium, creating buildings with the lowest possible impact on the environment is now possible.

Swedish rapeseed oil colour coating

Most GreenCoat® colour coated steel products feature a sustainable coating like none other found in the building industry. Using a substantial portion of Swedish rapeseed oil instead of fossil oil, this patented Bio-based Technology (BT) coating launched in 2012 is the only one on the market made from natural ingredients for exterior building applications like roofs and façades. This helps to drastically lower the environmental footprint of a building.

In addition, the coating is also chromate free according to REACH regulations, safe to handle, releases no harmful emissions and offers proven, long lasting performance on buildings for many decades to come.

GreenCoat® in brief

- High colour retention and long lasting finishes that resist rust, white rust and UV radiation as well as scratches and the build-up of dirt, for reduced maintenance.
- Highly formable and can easily be pressed, bent, cut, punched and profiled, allowing for the creation of complex shapes.
- Some GreenCoat® products can be formed at temperatures below zero, allowing for year round installation and lower costs.
- Coatings with tight colour tolerances ensuring batch-to-batch colour consistency.
- Extensive performance and finish guarantees.

Colours GreenCoat®

PLX & FAP in shiny gloss 40



RAL 9006 NCS -



RAL 9007 NCS -



RAL 7016 NCS S 7502-B



Dark grey 087 **RAL** 7043 NCS S 7005-B20G



PLX gloss 10

Anthracite grey 035 RAL 7016 NCS S 7502-B



Brown 434 **RAL** 8017 NCS S 8010-Y70R

Black 015 **RAL 9011**



Tile red 742 **RAL** 8004 NCS S 4550-Y70R



Dark red 758 **RAL 3009** NCS S 5040-Y80R

PLX & FAP in matt gloss 10



NCS S 9000-N

Goosewing grey 461 RAL 7038 NCS S 3502-Y



RAL 9006 NCS -



Silver metallic 045 Anhtracite metallic 044 **RAL 9007** NCS -



Led grey 036 RAL 7024 NCS S 7502-B



NCS S 7005-B20G



RAL 3009 NCS S 5040-Y80R



Black 015 RAL 9011 NCS S 9000-N



Coffee brown 387 **RAL 8019** NCS S 8005-Y80R



Forest green 874 RAL 6003 NCS S 6020-G30Y



RAL 8004 NCS S 4550-Y70R



Verdigris 975 RAL 6021 NCS S 3020-G10Y

FAP in shiny gloss 40 (not available in PLX)



White 020 RAL 9010 NCS S 0502-Y



Led grey 036 RAL 7024 NCS S 7502-B



Antique white 001 ŘAL 9002 NCS S 1002-G50Y



Brown 434 **RAL 8017** NCS S 8010-Y70R



Light grey 022 RAL 7044 NCS S 2005-G60Y



Azure blue 558 **RAL** 5009 NCS S 5030-R90B



Zinc grey 244 RAL 7040 NCS S 4005-R80B

Lindab DuraFrost® Pro

A scratch resistant coating with an exclusive glittery, wrinkled and matt surface

Lindab DuraFrost® Pro in PLX is SSAB GreenCoat® Pural, a wrinkled pural (polyurethane), where a substantial part of the solvents has been replaced by renewable alternatives, most commonly Swedish rapeseed oil. The nominal coating thickness is 50 µm. The textured paint which gets wrinkled during the curing process, makes the surface more scratch resistant com-pared to a smooth coating and the coating is optimized for good wear resistance.

Lindab DuraFrost® Pro is a matt product with a gloss as low as 5. Standard widths are 610 mm and 1250 mm.

Colours

Always mount the DuraFrost® Pro in the same direction, arrows can be found on the backside coating. The structure in the material can otherwise brake the light in different ways, with an experienced colour difference as a result.

Never mix material from different batches on the same roof or wall side.

Warranties

Read more about warranty periods on lindabprofile.co.uk





Lindab Magestic

Steel metal coated with zinc-magnesium

Lindab Magestic is a newly developed and more advanced rust protection than normal galvanized. The durable material also ages in style. It is delivered in ZM310, meaning 310 grams per m^2 and double side. Equivalent to 24 μm coating on each side. Lindab Magestic will patinate over time. It can end up being dark grey, and already after a couple of months outside you can usually see how it has started to darken which gives a rustic and genuine feeling.

Warranties

Read more about warranty periods on lindabprofile.co.uk







6 months



4 years Depending on environment







Accessories



Clipdriver

Automatic tool for clip fastening of sheet steel roofing. High and even quality with identical clip installation every time. Ergonomic and fast installation gives large savings in time and money with Bjarnes System Clipdriver



System for insulated roofs with Bjarnes the Krabban clip

The Krabban clip fixes standing seam roof sheets to insulated roofs for all materials.



Elite 300 Underlay

Medium weight vapour-permeable roofing underlay. Supplied in 1.5 m x 50 m rolls.



Bjarnes System Clips

Dependable and tested clips for fixing in all types of standing seam roof and substrates.



Lindab No1 Clips

The sliding clip No1 has a captive screw, which speeds up and simplifies fitting.



The steel trolley

With the steel trolley, strip coils can be moved simply and ergonomically. The trolley can also serve as an efficient uncoiler. For weights up to 400 kg.



Protective film

With a protective film on the steel sheets, the material is protected during transport, working and against scratches made by other occupational groups on the roof. You can finish all the work before you take off the film. The film must be removed within 6 months from application though.



Most of us spend the majority of our time indoors. Indoor climate is crucial to how we feel, how productive we are and if we stay healthy.

We at Lindab have therefore made it our most important objective to contribute to an indoor climate that improves people's lives. We do this by developing energy-efficient ventilation solutions and durable building products. We also aim to contribute to a better climate for our planet by working in a way that is sustainable for both people and the environment.

Lindab | For a better climate

