



Data sheet
testo 405i

Thermal anemometer operated with smartphone

testo 405i

Compact professional measuring instrument from the Testo Smart Probes series, for use with smartphones/tablets

Measurement of air flow velocity, temperature and volume flow

Easy configuration (dimensions and geometry) of the duct cross-section for determining volume flow

Measurement data analyzed and sent via testo Smart App

Telescopic shaft, extendable up to 400 mm

Space-saving and easy to transport



Bluetooth
+ App

testo Smart App
for free download



The hot-wire anemometer testo 405i, in combination with a smartphone or tablet, is a compact measuring instrument for air flow velocities, temperatures and volume flows. Equipped with a telescopic shaft, extendable to 400 mm, it allows flexible applications in rooms and ducts. Via the testo Smart App installed on the end device, users can comfortably read off their measurement values, configure volume flow measurements quickly and easily, and reliably determine timed and multi-point mean values.


The measurement protocols can then be directly sent as PDF or Excel files. In combination with the thermal hygrometer testo 605i, the testo 405i is suitable for determining cooling or heating performance.



Technical data/accessories

testo 405i


testo 405i, thermal anemometer operated with smartphone, incl. batteries and calibration protocol



Order no. 0560 1405

testo Smart App

The App turns your smartphone/tablet into the display of the testo 405i. The operation of the measuring instrument as well as the display of the measurement values take place by Bluetooth via the Testo Smart App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.



Sensor type	Hot wire
Measuring range	0 to 30 m/s
Accuracy ±1 digit	±(0.1 m/s + 5 % of m.v.) (0 to 2 m/s) ±(0.3 m/s + 5 % of m.v.) (2 to 15 m/s) ±(0,5 m/s + 5 % of m.v.) (15 to 30 m/s)
Resolution	0.01 m/s

Sensor type	NTC
Measuring range	-20 to +60 °C
Accuracy ±1 digit	±0.5 °C
Resolution	0.1 °C

General technical data

Compatibility	requires iOS 11.0 or newer / Android 6.0 or newer requires mobile end device with Bluetooth 4.0
Storage temperature	-20 to +60 °C
Operating temperature	-20 to +50 °C
Battery type	3 micro batteries AAA
Battery life	15 hrs
Dimensions	200 x 30 x 41 mm Telescope extendable to 400 mm

Accessories

Order no.

testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i, dimensions 270 x 190 x 60 mm	0516 0260	
ISO calibration certificate flow velocity, two-point calibration, calibration points 5; 10 m/s	0520 0094	
ISO calibration certificate flow velocity, hot-wire/vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004	

Lindab Ltd

Lindab Ventilation Branches

Aberdeen	01224 708582	Exeter	01626 835032	Manchester	0161 876 0688
Basildon	01268 532016	Gateshead	0191 482 5995	Norwich	01603 747532
Belfast	02890 781607	Glasgow	0141 419 3800	Nottingham	0115 985 1923
Birmingham	0121 552 6100	High Wycombe	01494 463490	Sheffield	0114 244 5444
Bristol	0117 977 1345	Kent	01474 579800	Southampton	02380 262111
Cardiff	02920 794503	Leeds	0113 297 1111	Stoke-on-Trent	01782 383460
Croydon	0208 603 0850	Leicester	0116 255 6044		
Enfield	0208 805 3656	Lincoln	01522 567087		

Email: sales@lindab.co.uk
Web: lindab.co.uk
Eshop: lindab.co.uk/eshop

© 2024 Lindab Ltd. is a registered trademark of Lindab Ltd, as are the designation of our product ranges. Lindab Ltd reserves the right to make alterations without prior notice.

Whilst every care has been taken in the preparation of this brochure, some changes may have occurred since publication. Lindab Ltd is not responsible for omissions or typographical errors.

