



Be sure. **testo**

Vane anemometer operated with smartphone

testo 410i

Compact professional measuring instrument from the Testo Smart Probes series, for use with smartphones/tablets

Measurement of air flow velocity, volume flow and temperature

Easy parameterization of the outlet for volume flow measurement (dimensions and geometry)

Presentation of the volume flow of several outlets for the purposes of regulating systems

Measurement data analyzed and sent via testo Smart App

Space-saving and easy to transport



Bluetooth
+ App

testo Smart App
for free download



The compact vane anemometer testo 410i, in combination with a smartphone or tablet, is suitable for measuring air flow velocity, volume flow and temperature at air outlets, and for regulating the air flow of a ventilation system. Via the testo Smart App installed on the end device, users can comfortably read off their measurement values, configure volume flow measurements quickly and easily, and reliably determine timed and multi-point mean values.


Especially useful: when regulating a ventilation system, you can compare the volume flows of several outlets. The measurement protocols can then be directly sent as PDF or Excel files.



Technical data/accessories

testo 410i


testo 410i, vane anemometer operated with smartphone, incl. batteries and calibration protocol



Order no. 0560 1410

testo Smart App

The App turns your smartphone/tablet into the display of the testo 410i. The operation of the measuring instrument as well as the display of the measurement values take place by Bluetooth via the testo Smart App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.



Sensor type	Vane
Measuring range	0.4 to 30 m/s
Accuracy ±1 digit	±(0.2 m/s + 2 % of m.v.) (0.4 to 20 m/s)
Resolution	0.1 m/s
Sensor type	NTC
Measuring range	-20 to +60 °C
Accuracy ±1 digit	±0.5 °C
Resolution	0.1 °C

General technical data	
Compatibility	requires iOS 11.0 or newer / Android 6.0 or newer requires mobile end device with Bluetooth 4.0
Storage temperature	-20 to +60 °C
Operating temperature	-20 to +50 °C
Battery type	3 micro batteries AAA
Battery life	130 hrs
Dimensions	154 x 43 x 21 mm 30 mm vane diameter

Accessories	Order no.
testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i, dimensions 270 x 190 x 60 mm	0516 0260
ISO calibration certificate flow velocity, two-point calibration, calibration points 5 m/s and 10 m/s	0520 0094
ISO calibration certificate flow velocity, hot-wire/vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034

Lindab Ltd

Lindab Ventilation Branches

Aberdeen	01224 708582	Exeter	01626 835032	Manchester	0161 876 0688
Basildon	01268 532016	Gateshead	0191 482 5995	Norwich	01603 747532
Belfast	02890 781607	Glasgow	0141 419 3800	Nottingham	0115 985 1923
Birmingham	0121 552 6100	High Wycombe	01494 463490	Sheffield	0114 244 5444
Bristol	0117 977 1345	Kent	01474 579800	Southampton	02380 262111
Cardiff	02920 794503	Leeds	0113 297 1111	Stoke-on-Trent	01782 383460
Croydon	0208 603 0850	Leicester	0116 255 6044		
Enfield	0208 805 3656	Lincoln	01522 567087		

Email: sales@lindab.co.uk
Web: lindab.co.uk
Eshop: lindab.co.uk/eshop

© 2024 Lindab Ltd. is a registered trademark of Lindab Ltd, as are the designation of our product ranges. Lindab Ltd reserves the right to make alterations without prior notice.

Whilst every care has been taken in the preparation of this brochure, some changes may have occurred since publication. Lindab Ltd is not responsible for omissions or typographical errors.

