



# Roof Screw | LS

## PRODUCT FEATURES

Torx T25 head roof screw for fastening to sheet metal and wood

Suitable for use with Krabban system for installing standing seam roofing systems made of aluminium, copper, steel sheet metal and zinc.

## PRODUCT DATA

|                          |                     |
|--------------------------|---------------------|
| Dimension:               | 4.8 mm              |
| Material:                | Coated carbon steel |
| Quality:                 | SS1370              |
| Drive:                   | Torx                |
| Point:                   | Drill bit           |
| Drill capacity:          | 2 x 1.25 mm         |
| Minimum anchoring depth: | 20 mm               |

## Characteristic pullout value

|         |       |
|---------|-------|
| 0.7 mm: | 1050N |
| 0.8 mm: | 1220N |

Steel plate (Minimum quality/yield point 350 MPa)

| Size   | Item no. | No./box |
|--------|----------|---------|
| 50 mm  | LS50     | 500     |
| 60 mm  | LS60     | 500     |
| 70 mm  | LS70     | 500     |
| 80 mm  | LS80     | 500     |
| 90 mm  | LS90     | 500     |
| 100 mm | LS100    | 500     |
| 110 mm | LS110    | 500     |
| 120 mm | LS120    | 500     |
| 130 mm | LS130    | 500     |
| 140 mm | LS140    | 500     |
| 150 mm | LS150    | 500     |
| 170 mm | LS170    | 500     |

